

## Forks & Brakes

# FORK OIL FACTORY LINE

Very Light-2.5W, Light-5W, Light-Medium-7.5W, Medium-10W

## SPECIFICATIONS



**F**ork Oil Factory Line is 100% synthetic, High Performance Hydraulic Fluid for any telescopic fork. Four viscosities: Very Light, Light, Light-Medium, Medium.

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by Motul.

Outstanding suspension performance as soon as riding and maintained performance in the time.

High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.

Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

Motul Fork Oil Factory Line can be mixed to obtain the suitable absorbing.

Use the exact quantity recommended by the fork manufacturer.

Use **linked** data to obtain suitable viscosity.



### Product

FORK OIL FACTORY LINE

### Feature

100% synthetic, Protects gaskets and makes sliding smoother. Anti-wear, anti-foam and anti-corrosion properties.

### SAE/DOT Standard

Very Light-2.5W, Light-5W, Light-Medium-7.5W, Medium-10W

### Specification

---

### Maker's Approval

---

### Compatibility

All upside-down telescopic front and cartridge telescopic front forks. For competition use.

[webmaster@motul.com.sg](mailto:webmaster@motul.com.sg)

Content, design and layout is Copyright ©2003  
HIGH-TECH LUBRICANTS AP PTE.LTD.

All Rights Reserved. Reproduction in whole or in part in any form or medium without the expressed written permission of HIGH-TECH LUBRICANTS AP PTE.LTD. is strictly prohibited.